## Data sheet

LOGO! TD TEXTDISPLAY, 6 LINES, 3 BACKGROUND COLORS, 2 ETHERNET PORTS, ACCESSORIES, FOR LOGO! 8



Figure similar

General information	
Product type designation	LOGO! TDE
Suitability for use	Can be used with LOGO! 8 and higher
Display	
Design of display	FSTN
Line display	
Number of lines	6
<ul> <li>Number of characters per line</li> </ul>	20
Backlighting	
Type of backlighting	LED
Control elements	
Keyboard fonts	
System keys	Yes
<ul> <li>Number of configurable system keys</li> </ul>	0
alphanumeric keyboard	No
Installation type/mounting	

Wall mounting/direct mounting	No
-	
Supply voltage	AC/DC
Type of supply voltage	
Rated value (DC)	12 V; 12/24 V DC, 24 V AC
Power loss	
Power loss, typ.	1.8 W; At 24 V DC
Interrupts/diagnostics/status information	
Diagnostic functions	No
-	
Degree and class of protection	IDAS.
IP (at the front)	IP65
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
FM approval	Yes
KC approval	Yes
Marine approval	
American Bureau of Shipping (ABS)	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	-20 °C; No condensation
• max.	55 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Altitude during operation relating to sea level	
Ambient air temperature-barometric pressure- altitude	Tmin Tmax at 1 080 hPa 795 hPa (-1 000 m +2 000 m)
Configuration	
Configuration software	
Configuration tool	LOGO! Soft Comfort V8
Accessories	
belongs to product	LOGO!
Mechanics/material	
Design of housing	plastic
Dimensions	
Width	128.2 mm
Height	86 mm
Depth Overall depth	38.7 mm 38.7 mm

Weights	
Weight, approx.	220 g
Scope of supply	
Delivery quantity in pieces	1
last modified:	01/10/2018